

View Online at <https://aerobasegroup.com/nsn/5925-01-523-1581>

Body Style:

Single pole type

Mounting Slot Width:

38.24 millimeters

Body Length:

73.41 millimeters

Body Width:

43.28 millimeters

Body Height:

46.58 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

58.64 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

58.64 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

28.62 millimeters

End Application:

Nsn 2320-01-447-6345; chassis, truck; w/s: family of medium and light tactical vehicles (fmtv)

Boss Height:

9.9 millimeters

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 slot

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

30.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

120.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0