

View Online at <https://aerobasegroup.com/nsn/5925-01-523-1917>

Body Style:

Multipole-single actuator type

Bushing Length:

6.5 millimeters

Body Length:

19.5 millimeters

Body Width:

45.0 millimeters

Body Height:

38.0 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

12.8 millimeters

Center To Center Distance Between Terminals Parallel To Width:

15.0 millimeters

End Application:

Alofts sonar system, model 980 (v1)

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations and 5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac all locations and 28.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations and 6000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

12.0 millimeters

Thread Pitch In Millimeters:

1.25

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct all locations and 10.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus proof and shockproof and vibrationproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Black push button

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Iso m

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0