

View Online at <https://aerobasegroup.com/nsn/5925-01-529-6189>

Thread Pitch Diameters:

+0.107/+0.138 inches

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.140 inches

Body Length:

2.490 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

0.740 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.060 inches

Mounting Surface To Terminal End Distance:

2.566 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 threaded stud

Maximum Continuous Load Current Rating Per Pole:

1.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip single location

Thread Size:

3.56 millimeters

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 100 pct single location

Special Features:

Vde approved; 50/60 hz short delay; legend: on/off i/o; black toggle handle

Frequency In Hertz:

50.0 single location or 60.0 single location

Thread Series Designator:

Iso m

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0