

View Online at <https://aerobasegroup.com/nsn/5925-01-530-4806>

Body Style:

Single pole type

Bushing Length:

0.625 inches

Body Length:

2.490 inches

Body Width:

0.750 inches

Body Height:

2.040 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

End Application:

Shelter, non-expandable, rigid wall, integrated.

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

60.0 amperes dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

60.000 single location

Manual Actuator Type And Quantity:

1 toggle

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 at 125 pct single location

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0