

View Online at <https://aerobasegroup.com/nsn/5925-01-534-3126>

Body Style:

Multipole-multiple actuator type

Body Length:

5.125 inches

Body Width:

3.108 inches

Center To Center Distance Between Terminals Parallel To Width:

1.026 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.750 inches

End Application:

Tactical air defense radar system (tadr)

Boss Height:

0.219 inches

Mounting Surface To Terminal End Distance:

3.485 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Actuator Function:

Trip-reset

Thread Size:

0.138 inches

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius all locations and 85.0 degrees celsius all locations

Special Features:

Terminal location back; series trip; time delay curve is long delay 25x inrush

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0