

View Online at <https://aerobasegroup.com/nsn/5925-01-534-8060>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

1.281 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.147 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Mounting Surface To Terminal End Distance:

1.780 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

3 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations and 50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

600.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 125 pct all locations and 5.000 at 125 pct all locations

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0