## NSN 5925-01-536-7196

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-536-7196 **Body Style:** Single pole type **Bushing Length:** 0.250 inches **Body Length:** 1.100 inches **Body Width:** 0.750 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.704 inches **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.375 inches **Nonturn Device Length:** 0.047 inches **Nonturn Device Width:** 0.078 inches **Fragility Factor:** Moderately rugged **End Application:** Nsn 1520-01-106-9519; helicopter, attack; w/s: helicopter, apache ah-64 **Mounting Surface To Terminal End Distance:** 1.218 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing **Storage Type:** General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32

**Maximum Continuous Load Current Rating Per Pole:** 

30.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:** 

120.0 ac single location

## NSN 5925-01-536-7196

Circuit Breaker - Page 2 of 2

A030a0



Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
2500.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.468 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct single location and 15.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
400.0 single location
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: