## NSN 5925-01-539-4044



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-539-4044 **Body Style:** Rectangular dimensional envelope **Overall Length:** 5.250 inches **Overall Height:** 3.0625 inches **Overall Width:** 2.000 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.196 inches **End Application:** Assualt hoseline system (ahs) **Pole Quantity: Mounting Facility Type And Quantity:** 4 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 40.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 277.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 14000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** 

**Actuator Position Designation:** 

At pole one

Trip-reset

## NSN 5925-01-539-4044

Circuit Breaker - Page 2 of 2



## Internal Trip Release Configuration: Series trip all locations Product Name: Ers hose reel base assembly Special Features: Molded case, thermal magnetic Frequency In Hertz: 60.0 all locations Terminal Type And Quantity: 4 compression Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A030a0