

View Online at <https://aerobasegroup.com/nsn/5925-01-541-7075>

Body Style:

Multipole-single actuator type

Bushing Length:

0.876 inches

Body Length:

5.800 inches

Body Width:

2.609 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.250 inches

Center To Center Distance Between Terminals Parallel To Width:

1.026 inches

End Application:

Amplifier unit, bpau

Mounting Surface To Terminal End Distance:

0.876 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 threaded hole

Maximum Continuous Load Current Rating Per Pole:

15.1 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

375.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

100.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Thread Size:

0.138 inches

Inclosure Protection Type For Which Designed:

Fungus proof and humidity resistant and shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

85.0 degrees celsius all locations

Product Name:

C series hydraulic-magnetic circuit breaker

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0