

View Online at <https://aerobasegroup.com/nsn/5925-01-543-8270>

Body Style:

Multipole-single actuator type

Bushing Length:

0.625 inches

Body Length:

1.562 inches

Body Width:

0.656 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

Center To Center Distance Between Terminals Parallel To Width:

0.875 inches

Unthreaded Mounting Hole Diameter:

0.391 inches

Mounting Surface To Terminal End Distance:

1.605 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

2.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Relay trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 100 pct all locations

Inclosure Protection Type For Which Designed:

Vibration resistant and moisture resistant and shock resistant

Switch Terminal Type:

Screw

Switch Voltage Rating And Type In Volts:

240.0 ac

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0