

View Online at <https://aerobasegroup.com/nsn/5925-01-543-8270>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.625 inches

**Body Length:**

1.562 inches

**Body Width:**

0.656 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.625 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.875 inches

**Unthreaded Mounting Hole Diameter:**

0.391 inches

**Mounting Surface To Terminal End Distance:**

1.605 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

2.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Relay trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.500 at 100 pct all locations

**Inclosure Protection Type For Which Designed:**

Vibration resistant and moisture resistant and shock resistant

**Switch Terminal Type:**

Screw

**Switch Voltage Rating And Type In Volts:**

240.0 ac

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0