

View Online at <https://aerobasegroup.com/nsn/5925-01-545-0437>

**Body Style:**

Single pole type

**Bushing Length:**

0.332 inches

**Body Length:**

1.562 inches

**Body Width:**

0.625 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**End Application:**

LAUN-CH-ING-STAT

**Mounting Surface To Terminal End Distance:**

1.810 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Maximum Continuous Load Current Rating Per Pole:**

9.0 amperes ac single location and 9.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location and 50.0 dc single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Thread Size:**

0.375 inches

**Product Name:**

Circuit breaker low power sealed

**Special Features:**

Voltage and frequency rating 50 v dc, and 240 v ac at 60 hz and 400 hz high inrush 800 percent at 60 hz and dc, 1, 400 percent at 400 hz

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0