

View Online at <https://aerobasegroup.com/nsn/5925-01-546-7914>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.625 inches

**Body Length:**

2.000 inches

**Body Width:**

1.515 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**End Application:**

Mcs In sw rk 48011322; machinery con

**Mounting Surface To Terminal End Distance:**

2.232 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.500 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.500 at 200 pct all locations and 20.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant and vibration resistant and salt spray proof and moisture resistant and explosion resistant and shock resistant

**Product Name:**

Mil spec: circuit breakers, magnetic, panel seal, trip-free, series trip, double pole

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

4 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0

**Mil-std (military Standard):**

spec.