NSN 5925-01-547-2880

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-547-2880 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.130 inches **Body Height:** 3.380 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.062 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.164 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **End Application:** Hemp endurable power system **Boss Height:** 0.125 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 300.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 125.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 65000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

NSN 5925-01-547-2880

Circuit Breaker - Page 2 of 2



Trin	Polosco	Ambiant	Tempurature	Dating:
un	Release	Ambient	remburature	Ratinu:

40.0 degrees celsius all locations

Product Name:

Molded case circuit breaker f-frame, 10-225 amp, type ed

Special Features:

Sealed with non-interchangable trip units; suitable for reverse feed use; includes terminals on load end only

Frequency In Hertz:

60.0 all locations or 50.0 all locations

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0