

View Online at <https://aerobasegroup.com/nsn/5925-01-547-2880>

Body Style:

Multipole-single actuator type

Body Length:

6.000 inches

Body Width:

4.130 inches

Body Height:

3.380 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.062 inches

Center To Center Distance Between Terminals Parallel To Width:

1.375 inches

Unthreaded Mounting Hole Diameter:

0.164 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

End Application:

Hemp durable power system

Boss Height:

0.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

300.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

65000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Product Name:

Molded case circuit breaker f-frame, 10-225 amp, type ed

Special Features:

Sealed with non-interchangeable trip units; suitable for reverse feed use; includes terminals on load end only

Frequency In Hertz:

60.0 all locations or 50.0 all locations

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0