

View Online at <https://aerobasegroup.com/nsn/5925-01-549-1403>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.240 inches

Body Length:

2.000 inches

Body Width:

1.515 inches

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

End Application:

Receiver, drt-1201b

Mounting Surface To Terminal End Distance:

2.075 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip all locations

Trip Release Duty Cycle:

Continuous all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

1.800 at 125 pct all locations and 100.000 at 125 pct all locations and 0.006 at 1000 pct all locations and 0.280 at 1000 pct all locations

Inclosure Protection Type For Which Designed:

Moisture resistant and salt spray proof

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius all locations and 85.0 degrees celsius all locations

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0