

View Online at <https://aerobasegroup.com/nsn/5925-01-550-4950>

**Body Style:**

Multipole-single actuator type

**Body Length:**

5.125 inches

**Body Width:**

3.138 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

3.550 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.026 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.026 inches

**End Application:**

Control cabinet assembly

**Boss Height:**

0.220 inches

**Mounting Surface To Terminal End Distance:**

3.600 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

100.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Product Name:**

E series handle ul recognized back connected circuit breaker

**Special Features:**

UI 1077/ul508 recognized & csa certified; actuator is black with white marking

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0