

View Online at <https://aerobasegroup.com/nsn/5925-01-552-2637>

**Body Style:**

Single pole type

**Mounting Slot Width:**

0.203 inches

**Body Length:**

6.000 inches

**Body Width:**

1.375 inches

**Body Height:**

3.125 inches

**Case Material:**

Plastic

**End Application:**

Radar tps-77

**Boss Height:**

0.250 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

4 slot

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic-hydraulic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.150 at 200 pct single location and 0.600 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Fungus resistant and humidity resistant and shock resistant and vibration resistant

**Special Features:**

Operating temperature range minus 40.0 to plus 85.0 degrees c; voltage rating 251.0 to 600.0 volts ac

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Terminal Type And Quantity:**

2 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0