

View Online at <https://aerobasegroup.com/nsn/5925-01-552-2638>

Body Style:

Single pole type

Mounting Slot Width:

0.203 inches

Body Length:

6.000 inches

Body Width:

1.375 inches

Body Height:

3.125 inches

Case Material:

Plastic

Boss Height:

0.250 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

4 slot

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 200 pct single location and 0.600 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and humidity resistant and shock resistant and vibration resistant

Special Features:

Operating temperature range minus 40.0 to plus 85.0 degrees c; voltage rating 251.0 to 600.0 volts ac

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0