

View Online at <https://aerobasegroup.com/nsn/5925-01-552-4945>

**Body Style:**

Multipole-single actuator type

**Mounting Slot Width:**

0.203 inches

**Body Length:**

6.000 inches

**Body Width:**

4.125 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

5.000 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.375 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.687 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.375 inches

**Boss Height:**

0.250 inches

**Mounting Surface To Terminal End Distance:**

3.125 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 slot

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

220.0 ac all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Internal Trip Release Configuration:**

Series/relay trip all locations

**Trip Release Duty Cycle:**

Intermittent all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.150 at 200 pct all locations and 0.600 at 200 pct all locations

**Special Features:**

2 electrically isolated coils; coil number 1 time delay; coil number 2 instantaneously tripped by curren (220.0 volts, 50.0 to 60.0 hertz, 30.0 va) , supplied by control equipment or remote monitoring system; ultimate trip rating for coil 2 is 120.0 percent

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0