

View Online at <https://aerobasegroup.com/nsn/5925-01-552-9323>

**Body Style:**

Multipole-single actuator type

**Body Width:**

5.340 inches

**Body Height:**

3.440 inches

**Case Material:**

Plastic

**Pole Quantity:**

4

**Maximum Continuous Load Current Rating Per Pole:**

200.0 amperes ac all locations and 200.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

65000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip w/separate reset

**Actuator Position Designation:**

At pole two

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Special Features:**

Dc ratings are of 2-poles of 3-pole circuit; trip unit - thermal and magnetic are adjustable; rated ultimate breaking capacities - 65000.0 amps at 220.0 to 240.0 volts ac; 25000.0 amps at 380.0 to 415.0 volts ac; 25000.0 amps at 480.0 volts ac; 18000.0 amps at 600.0 volts ac; 12000.0 amps at 690.0 volts ac; 10000.0 amps at 250.0 volts dc; height 7.000 inches ; includes freeze tested option (f02) using special lubrication, mechanical operation is verified to minus 40.0 degrees c; also includes standard shunt trip option (snt120cpk) 120.0 volts ac. 50.0 to 60.0 hertz, 110.0 to 125.0 volts dc. Mounted in right-hand cavity left pole position

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A030a0