

View Online at <https://aerobasegroup.com/nsn/5925-01-558-6304>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

Between 0.219 inches and 0.281 inches

**Body Length:**

0.781 inches

**Body Width:**

1.840 inches

**Body Height:**

1.381 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.469 inches and 0.531 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.593 inches and 0.655 inches

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

200.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

120.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.438 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

4.000 at 200 pct all locations and 20.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Shockproof and vibrationproof

**Trip Release Ambient Temperature Rating:**

71.0 degrees fahrenheit all locations

**Special Features:**

Extra long push button

**Frequency In Hertz:**

400.0 all locations

**Test Data Document:**

81349-mil-c-5809 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

6 tab w/screw

**Specification Data:**

96906-ms14154 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0