NSN 5925-01-564-3707

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-564-3707

Body Style:
Single pole type
Body Length:
1.950 inches
Body Width:
0.750 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.530 inches
Unthreaded Mounting Hole Diameter:
0.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.660 inches
End Application:
5793209 (31442), emergency pwr panl ay; advanced seal delivery system obrps list; packup kit/critical spares
Mounting Surface To Terminal End Distance:
2.032 inches
Pole Quantity:
2
Mounting Facility Type And Quantity:
2 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
0.7 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
65.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
1000.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Nontrip free
Internal Trip Release Configuration:

Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct single location and 20.000 at 200 pct single location

NSN 5925-01-564-3707

Circuit Breaker - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0