

View Online at <https://aerobasegroup.com/nsn/5925-01-564-3707>

Body Style:

Single pole type

Body Length:

1.950 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

End Application:

5793209 (31442), emergency pwr panl ay; advanced seal delivery system obrps list; packup kit/critical spares

Mounting Surface To Terminal End Distance:

2.032 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

0.7 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct single location and 20.000 at 200 pct single location

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0