NSN 5925-01-566-7983

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-566-7983

Body Style:

Multipole-single actuator type

Body Length:

2.490 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.060 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

4920-01-465-7013

Boss Height:

1.940 inches

Mounting Surface To Terminal End Distance:

0.655 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overvoltage all locations

Trip Release Method:

Solid state all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-01-566-7983

Circuit Breaker - Page 2 of 2



Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 125 pct all locations and 120.000 at 125 pct all locations

Product Name:

Circuit breaker

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Test Data Document:

81541-852-503-55 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--Demilitarization:

No

Fiig:

A030a0