

View Online at <https://aerobasegroup.com/nsn/5925-01-567-5134>

**Body Style:**

**Bushing Length:**

0.380 inches

**Body Length:**

1.562 inches

**Body Width:**

0.656 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.875 inches

**End Application:**

An/bqq-1 (v) unit 4190 ti06 ph3, hf operator

**Mounting Surface To Terminal End Distance:**

1.605 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Features Provided:**

Neutral pole, switchable

**Maximum Continuous Load Current Rating Per Pole:**

10000.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc single location and 240.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

40000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

800.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal single location

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3.000 at 135 pct single location and 60.000 at 135 pct single location

**Product Name:**

Cage: ap/up magnetic circuit protector

**Special Features:**

Auxiliary switch rating: 0.5 amp at 120 vac or 50 vdc

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Supplementary Features:**

Fully sealed; waterproof panel integrity provided by o-ring bushing seal and silicon rubber gland within bushing/handle assembly

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0