

View Online at <https://aerobasegroup.com/nsn/5925-01-567-5307>

Body Style:

Single pole type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

0.656 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

End Application:

An/bqq-1 (v) unit 4190 ti06 ph3, hf operator csl

Mounting Surface To Terminal End Distance:

1.605 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Features Provided:

Neutral pole, switchable

Maximum Continuous Load Current Rating Per Pole:

5000.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location and 240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

800.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 135 pct single location and 60.000 at 135 pct single location

Product Name:

Cage: ap/up magnetic circuit protector

Special Features:

Auxiliary switch rating: 0.5 amp at 120 vac or 50 vdc

Frequency In Hertz:

50.0 single location or 60.0 single location

Supplementary Features:

Fully sealed; waterproof panel integrity provided by o-ring bushing seal and silicon rubber gland w/in bushing/handle assembly

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook and 3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0