NSN 5925-01-567-9123

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-567-9123

### **Body Style:**

Multipole-multiple actuator type

#### **Bushing Length:**

0.240 inches

# **Body Length:**

2.000 inches

#### Body Width:

1.515 inches

#### **Case Material:**

Metal

#### Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

## **End Application:**

Boat, patrol, 34 foot, 34pb0601 through 34pb0609 and 34pb0701

## Mounting Surface To Terminal End Distance:

2.075 inches

#### **Pole Quantity:**

2

## Mounting Facility Type And Quantity:

4 unthreaded hole

# Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations and 5.0 amperes dc all locations

# Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 80.0 dc all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations and 7500.0 dc all locations

# Circuit Protection Type:

Overcurrent all locations

# Trip Release Method:

Magnetic all locations

# Trip Release Characteristic:

Time delay all locations

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 all locations

# NSN 5925-01-567-9123

Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
1.000 at 200 pct all locations and 20.000 at 200 pct all locations
Product Name:
Cage: iug magnetic circuit protector
Special Features:
Screw terminals are bent in 30 degrees; screws are 0.313 in. Long and are no. 10-30 with captive washers
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0