

View Online at <https://aerobasegroup.com/nsn/5925-01-567-9148>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

0.240 inches

**Body Length:**

2.000 inches

**Body Width:**

1.515 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**End Application:**

Boat, patrol, 34 foot, 34pb0601 through 34bp0609 and 34bp0701

**Mounting Surface To Terminal End Distance:**

2.075 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations and 10.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 80.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10.0 ac all locations and 10.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

1000.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.000 at 200 pct all locations and 20.000 at 200 pct all locations

**Product Name:**

Cage: iug magnetic circuit protector

**Special Features:**

Screw terminals are bent in 30 deg; screws are 0.313 in. And are no. 10-30 with captive washers

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0