

View Online at <https://aerobasegroup.com/nsn/5925-01-567-9609>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.240 inches

Body Length:

2.000 inches

Body Width:

1.515 inches

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

End Application:

Boat, patrol, 34 foot, 34pb0601 through 34bp0609 and 34bp0701

Mounting Surface To Terminal End Distance:

2.075 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations and 15.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 80.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct all locations and 20.000 at 200 pct all locations

Special Features:

Screw terminals are bent in 30 degrees; screws are 0.313 in. Long and are no. 10-30 with captive washers

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0