# NSN 5925-01-567-9668

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-567-9668

#### **Body Style:**

Multipole-multiple actuator type

### **Bushing Length:**

0.240 inches

# **Body Length:**

2.000 inches

#### **Body Width:**

1.515 inches

#### **Case Material:**

Metal

#### Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

### **End Application:**

Boat, patrol, 34 foot, 34bp0601 through 34bp0609 and 34bp0701

# Mounting Surface To Terminal End Distance:

2.075 inches

#### **Pole Quantity:**

2

#### Mounting Facility Type And Quantity:

2 unthreaded hole

#### Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations and 20.0 amperes dc all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 80.0 dc all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations and 7500.0 dc all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Magnetic all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 all locations

# **NSN 5925-01-567-9668** Circuit Breaker - Page 2 of 2



| Reset Method:  |
|--|
| Manual   |
| Main Contact Tripping Mechanism Type:  |
| Trip free  |
| Manual Actuator Type And Quantity:   |
| 1 toggle   |
| Actuator Position Designation:   |
| At pole one  |
| Internal Trip Release Configuration:   |
| Series trip all locations  |
| Trip Delay Time In Seconds Per Rated Continuous Current:   |
| 1.000 at 200 pct all locations and 20.000 at 200 pct all locations                                   |
| Product Name:  |
| Cage: iug magnetic circuit protector   |
| Special Features:  |
| Screw terminals are bent in 30 deg; screws are 0.313 in. Long and are no. 10-30 with captive washers |
| Frequency In Hertz:  |
| 60.0 all locations   |
| Terminal Type And Quantity:  |
| 2 screw  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A030a0   |
|  |