

View Online at <https://aerobasegroup.com/nsn/5925-01-575-1503>

Body Style:

Multipole-single actuator type

Case Material:

Plastic

Pole Quantity:

4

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac all locations and 480.0 ac all locations

Trip Release Method:

Magnetic all locations

Reset Method:

Manual and electric

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal and remote trip feature all locations

Reset Actuator Voltage Rating And Type In Volts:

120.0 ac and 120.0 dc

Inclosure Protection Type For Which Designed:

Dustproof

Product Name:

Magnetic circuit protector

Special Features:

Stainless steel springs no.10-32 threaded studs, hex nut and 2 flat washers on each terminal; auxiliary switch 110 quick connect or solder terminals; dust sealed protector; white handle; inertial delay

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Precious Material And Location:

Contact gold

Precious Material:

Gold

Special Test Features:

Mil-std-202 methods 101, 106, 204 and 213

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

Mil-std (military Standard):

Mil-std-202 spec.