

View Online at <https://aerobasegroup.com/nsn/5925-01-575-1503>

**Body Style:**

Multipole-single actuator type

**Case Material:**

Plastic

**Pole Quantity:**

4

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

277.0 ac all locations and 480.0 ac all locations

**Trip Release Method:**

Magnetic all locations

**Reset Method:**

Manual and electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal and remote trip feature all locations

**Reset Actuator Voltage Rating And Type In Volts:**

120.0 ac and 120.0 dc

**Inclosure Protection Type For Which Designed:**

Dustproof

**Product Name:**

Magnetic circuit protector

**Special Features:**

Stainless steel springs no.10-32 threaded studs, hex nut and 2 flat washers on each terminal; auxiliary switch 110 quick connect or solder terminals; dust sealed protector; white handle; inertial delay

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Precious Material And Location:**

Contact gold

**Precious Material:**

Gold

**Special Test Features:**

Mil-std-202 methods 101, 106, 204 and 213

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0

**Mil-std (military Standard):**

Mil-std-202 spec.