

View Online at <https://aerobasegroup.com/nsn/5925-01-575-6956>

Body Style:

Multipole-single actuator type

Overall Length:

1.375 inches

Body Width:

1.304 inches

Case Material:

Plastic

End Application:

C-10256c/brr-6 trident, control indicator; c-10256d/brr-6 trident, control indicator; ohio class ssbn

Pole Quantity:

1

Mounting Facility Type And Quantity:

4 terminal

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct all locations and 8.000 at 200 pct all locations

Product Name:

Cage: snapak series magnetic circuit protector

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

4 knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A030a0