

View Online at <https://aerobasegroup.com/nsn/5925-01-575-7054>

**Body Style:**

Multipole-single actuator type

**Overall Length:**

1.375 inches

**Overall Diameter:**

1.304 inches

**Case Material:**

Plastic

**End Application:**

10256c/brr-6 trident, control indicator; 10256d/brr-6 trident, control indicator

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

1.000 at 200 pct all locations and 8.000 at 200 pct all locations

**Product Name:**

Cage: snapak series magnetic circuit protector, push-pull, 2 pole, fast delay dc-50/60hz, black, no outer hardware desired, horizontal mount, vde and ccc approved

**Special Features:**

Push-pull actuator has white band visible in off position onl; knife blade terminals are 0.375 in. Long with single hole

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 knife blade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A030a0