

View Online at <https://aerobasegroup.com/nsn/5925-01-575-7054>

Body Style:

Multipole-single actuator type

Overall Length:

1.375 inches

Overall Diameter:

1.304 inches

Case Material:

Plastic

End Application:

10256c/brr-6 trident, control indicator; 10256d/brr-6 trident, control indicator

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct all locations and 8.000 at 200 pct all locations

Product Name:

Cage: snapak series magnetic circuit protector, push-pull, 2 pole, fast delay dc-50/60hz, black, no outer hardware desired, horizontal mount, vde and ccc approved

Special Features:

Push-pull actuator has white band visible in off position onl; knife blade terminals are 0.375 in. Long with single hole

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A030a0