

View Online at <https://aerobasegroup.com/nsn/5925-01-578-0727>

**Body Style:**

Single pole type

**Bushing Length:**

0.250 inches

**Body Length:**

0.780 inches

**Body Width:**

0.591 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.504 inches

**End Application:**

An/vlq-1 (v) 1, countermeasure set

**Mounting Surface To Terminal End Distance:**

1.440 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes ac single location and 40.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac single location and 28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

4000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.438 inches

**Trip Release Ambient Temperature Rating:**

23.0 degrees celsius single location

**Product Name:**

Cage: high performance thermal circuit breaker 483-

**Frequency In Hertz:**

400.0 single location

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A030a0