

View Online at <https://aerobasegroup.com/nsn/5925-01-578-2068>

Body Style:

Multipole-multiple actuator type

Body Length:

61.5 millimeters

Body Width:

52.5 millimeters

Body Height:

80.0 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

17.5 millimeters

End Application:

Operator control assembly and parts list (receiving area), 55 ton and 56 ton cask controls

Boss Height:

5.5 millimeters

Pole Quantity:

3

Mounting Facility Type And Quantity:

Din rail

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

415.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

10.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Product Name:

Cage: 1492-sp series c supplementary protectors/miniature circuit breaker

Frequency In Hertz:

50.0 all locations or 60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0