

View Online at <https://aerobasegroup.com/nsn/5925-01-578-5971>

Body Style:

Single pole type

Bushing Length:

0.400 inches

Body Length:

1.375 inches

Body Width:

0.680 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.125 inches

End Application:

C-10257b/brr-6 trident, control indicator

Mounting Surface To Terminal End Distance:

1.960 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

800.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

1.000 at 200 pct single location and 15.000 at 200 pct single location

Product Name:

Snapak series magnetic circuit protector

Special Features:

Vde and ccc approved

Frequency In Hertz:

50.0 single location or 60.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 knife blade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0