

View Online at <https://aerobasegroup.com/nsn/5925-01-580-7166>

**Body Style:**

Single pole type

**Bushing Length:**

0.625 inches

**Body Length:**

1.562 inches

**Body Width:**

0.656 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

0.875 inches

**End Application:**

00341000-02 (8x691), radar processor controller

**Mounting Surface To Terminal End Distance:**

1.605 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Maximum Continuous Load Current Rating Per Pole:**

2.5 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

65.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

50.0 dc single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

65.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/remote trip feature single location

**Thread Size:**

0.375 inches

**Trip Release Duty Cycle:**

Continuous single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct single location

**Product Name:**

Ap magnetic circuit protector

**Special Features:**

50/60 hz high pulse long time delay; inertial delay; auxilliary switch

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0