

View Online at <https://aerobasegroup.com/nsn/5925-01-580-7166>

Body Style:

Single pole type

Bushing Length:

0.625 inches

Body Length:

1.562 inches

Body Width:

0.656 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

End Application:

00341000-02 (8x691), radar processor controller

Mounting Surface To Terminal End Distance:

1.605 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Maximum Continuous Load Current Rating Per Pole:

2.5 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

65.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Auxiliary Trip Coil Voltage Type And Rating In Volts:

50.0 dc single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

65.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip w/remote trip feature single location

Thread Size:

0.375 inches

Trip Release Duty Cycle:

Continuous single location

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location

Product Name:

Ap magnetic circuit protector

Special Features:

50/60 hz high pulse long time delay; inertial delay; auxilliary switch

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0