

View Online at <https://aerobasegroup.com/nsn/5925-01-582-4348>

**Body Style:**

Multipole-single actuator type

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac all locations and 10.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

200.0 ac all locations and 28.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2500.0 ac all locations and 6000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Thread Size:**

6.0 millimeters

**Inclosure Protection Type For Which Designed:**

Humidity resistant and shock resistant and vibration resistant

**Trip Release Ambient Temperature Rating:**

-55.0 degrees celsius all locations and 90.0 degrees celsius all locations

**Product Name:**

High performance thermal circuit breaker

**Frequency In Hertz:**

400.0 all locations

**Supplementary Features:**

Item has auxiliary contact (n/c) (connector to en 3155-016m2018, size 20); barrier included (19.5 wide and 37.7 long-both mm; volt drop per pole 190 mv

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0