NSN 5925-01-582-6516

Circuit Breaker - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5925-01-582-6516

Body Style:Single pole typeBushing Length:0.470 inchesBody Length:0.781 inchesBody Width:0.593 inchesCenter To Center Distance Between Terminals Parallel To Length:0.500 inchesMounting Surface To Terminal End Distance:1.343 inchesPole Quantity:11Mounting Facility Type And Quantity:1 threaded bushingThready Qty Per Inch (tpi):2aMaximum Continuous Load Current Rating Per Pole:25.0 amperes dc single locationOperating Voltage Type And Rating Per Pole In Volts:28.0 dc single locationThread Size:0.0.3 dc single locationThread Size:0.3.7 inchesThread Size:0.3.7 inchesThread Size:0.3.7 inchesThread Size:0.4.7 inche		
Bushing Length: 0.470 inches Body Length: 0.781 inches Body Width: 0.593 inches Center To Center Distance Between Terminals Parallel To Length: 0.500 inches Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.000. dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000. dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Body Style:	
0.470 inclesBody Length:0.781 inclesBody Width:0.593 inclesCenter To Center Distance Between Terminals Parallel To Length:0.500 inclesMounting Surface To Terminal End Distance:1.343 inclesPole Quantity:1Mounting Facility Type And Quantity:1 threaded bushingThready Qty Per Inch (tpi):2aMaximum Continuous Load Current Rating Per Pole:25.0 amperes de single locationOperating Voltage Type And Rating Per Pole In Volts:28.0 do single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Ampers6000.0 de single locationThread Size:0.437 inchesThread Series Designator:UnTerminal Type And Quantity:2 screwShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Single pole type	
Body Length:0.781 inchesBody Width:0.593 inchesCenter To Center Distance Between Terminals Parallel To Length:0.500 inchesMounting Surface To Terminal End Distance:1.343 inchesPole Quantity:1Mounting Facility Type And Quantity:1 threaded bushingThready Qty Per Inch (tpi):2aMaximum Continuous Load Current Rating Per Pole:25.0 amperes dc single locationOperating Voltage Type And Rating Per Pole In Volts:28.0 dc single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Ampe:6000.0 dc single locationThread Series Designator:UnTerminal Type And Quantity:2 screwShelf Life:NaUnit Of Measure:-<	Bushing Length:	
0.781 inchesBody Width:0.593 inchesCenter To Center Distance Between Terminals Parallel To Length:0.500 inchesMounting Surface To Terminal End Distance:1.343 inchesPole Quantity:1Mounting Facility Type And Quantity:1 threaded bushingThready Qty Per Inch (tpi):2aMaximum Continuous Load Current Rating Per Pole:25.0 amperes dc single locationOperating Voltage Type And Rating Per Pole In Volts:28.0 dc single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Amps:6000.0 dc single locationThread Size:0.437 inchesThread Series Designator:UnTerminal Type And Quantity:2 screwShelf Life:NaUnt Of Measure:-Pomilitarization:NoFig:	0.470 inches	
Body Width: 0.593 inches Center To Center Distance Between Terminals Parallel To Length: 0.500 inches Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes de single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 de single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Ampes: 6000.0 de single location Thread Size: 0.437 inches Thread Series Designator: Un 2 screw Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fig:	Body Length:	
0.593 inches Center To Center Distance Between Terminals Parallel To Length: 0.500 inches Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	0.781 inches	
Center To Center Distance Between Terminals Parallel To Length: 0.500 inches Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Width:	
0.500 inchesMounting Surface To Terminal End Distance:1.343 inchesPole Quantity:1Mounting Facility Type And Quantity:1 threaded bushingThready Qty Per Inch (tpi):2aMaximum Continuous Load Current Rating Per Pole:25.0 amperes dc single locationOperating Voltage Type And Rating Per Pole In Volts:28.0 dc single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Amps:6000.0 dc single locationThread Size:0.437 inchesThread Series Designator:Un2 screwShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	0.593 inches	
Mounting Surface To Terminal End Distance: 1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Center To Center Distance Between Terminals Parallel To Length:	
1.343 inches Pole Quantity: 1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	0.500 inches	
Pole Quantity: 1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Surface To Terminal End Distance:	
1 Mounting Facility Type And Quantity: 1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Stelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.343 inches	
Mounting Facility Type And Quantity:1 threaded bushingThready Qty Per Inch (tpi):2aMaximum Continuous Load Current Rating Per Pole:25.0 amperes dc single locationOperating Voltage Type And Rating Per Pole In Volts:28.0 dc single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Amps:6000.0 dc single locationThread Size:0.437 inchesThread Series Designator:Un2 screwShelf Life:NaUnit Of Measure:Demilitarization:NoFig:	Pole Quantity:	
1 threaded bushing Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1	
Thready Qty Per Inch (tpi): 2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fiig:	Mounting Facility Type And Quantity:	
2a Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	1 threaded bushing	
Maximum Continuous Load Current Rating Per Pole: 25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	Thready Qty Per Inch (tpi):	
25.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2a	
Operating Voltage Type And Rating Per Pole In Volts:28.0 dc single locationMaximum Interrupting Capacity Current Type And Rating Per Pole In Amps:6000.0 dc single locationThread Size:0.437 inchesThread Series Designator:UnTerminal Type And Quantity:2 screwShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Maximum Continuous Load Current Rating Per Pole:	
28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	25.0 amperes dc single location	
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No	Operating Voltage Type And Rating Per Pole In Volts:	
6000.0 dc single location Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	28.0 dc single location	
Thread Size: 0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Maximum Interrupting Capacity Current Type And Rating Per Pole In A	mps:
0.437 inches Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	6000.0 dc single location	
Thread Series Designator: Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Size:	
Un Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.437 inches	
Terminal Type And Quantity: 2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:	
2 screw Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Un	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:	
N/a Unit Of Measure: Demilitarization: No Fiig:	2 screw	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
-	No	
A030a0	Fiig:	
	A030a0	