

View Online at <https://aerobasegroup.com/nsn/5925-01-585-0063>

Body Style:

Single pole type

Bushing Length:

Between 0.313 inches and 0.375 inches

Body Length:

2.187 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 0.875 inches and 0.937 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.781 inches and 1.843 inches

End Application:

Spanish air force

Mounting Surface To Terminal End Distance:

Between 1.281 inches and 1.343 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location and 3.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

4000.0 ac single location and 3500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Internal Trip Release Configuration:

Series trip single location

Thread Size:

6.0 millimeters

Trip Delay Time In Seconds Per Rated Continuous Current:

40.000 at 200 pct single location and 200.000 at 200 pct single location and 3.000 at 400 pct single location and 26.000 at 400 pct single location and 1.000 at 600 pct single location and 12.000 at 600 pct single location

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius single location and 71.0 degrees celsius single location

Product Name:

Drawing: 7271-3 type push-pull trip-free circuit breaker

Special Features:

Push-pull actuator marked with amp rating (3) on top

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0