

View Online at <https://aerobasegroup.com/nsn/5925-01-585-0063>

**Body Style:**

Single pole type

**Bushing Length:**

Between 0.313 inches and 0.375 inches

**Body Length:**

2.187 inches

**Body Width:**

0.750 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.875 inches and 0.937 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.781 inches and 1.843 inches

**End Application:**

Spanish air force

**Mounting Surface To Terminal End Distance:**

Between 1.281 inches and 1.343 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac single location and 3.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location and 30.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

4000.0 ac single location and 3500.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

6.0 millimeters

**Trip Delay Time In Seconds Per Rated Continuous Current:**

40.000 at 200 pct single location and 200.000 at 200 pct single location and 3.000 at 400 pct single location and 26.000 at 400 pct single location and 1.000 at 600 pct single location and 12.000 at 600 pct single location

**Trip Release Ambient Temperature Rating:**

-40.0 degrees celsius single location and 71.0 degrees celsius single location

**Product Name:**

Drawing: 7271-3 type push-pull trip-free circuit breaker

**Special Features:**

Push-pull actuator marked with amp rating (3) on top

**Frequency In Hertz:**

400.0 single location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0