NSN 5925-01-590-1623

Circuit Breaker - Page 1 of 2

Automatic and manual



View Online at https://aerobasegroup.com/nsn/5925-01-590-1623

Body Style:
Multipole-single actuator type
Body Length:
7.520 inches
Body Width:
4.120 inches
Body Height:
3.440 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.520 inches
Center To Center Distance Between Terminals Parallel To Width:
1.380 inches
Unthreaded Mounting Hole Diameter:
0.200 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.920 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.380 inches
Boss Height:
0.570 inches
Pole Quantity:
Pole Quantity: 3
-
3
3 Mounting Facility Type And Quantity:
3 Mounting Facility Type And Quantity: 2 unthreaded hole
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole:
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts:
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations Circuit Protection Type:
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations Circuit Protection Type: Overcurrent all locations
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic:
Mounting Facility Type And Quantity: 2 unthreaded hole Maximum Continuous Load Current Rating Per Pole: 225.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 14000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic: Instantaneous all locations

NSN 5925-01-590-1623

Circuit Breaker - Page 2 of 2



Fiig: A030a0