

View Online at <https://aerobasegroup.com/nsn/5925-01-591-0205>

Body Style:

Single pole type

Overall Length:

1.379 inches

Overall Width:

0.571 inches

Case Material:

Plastic

Mounting Surface To Terminal End Distance:

1.693 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location and 20.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location and 250.0 ac single location and 32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac single location and 2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

5.000 at 800 pct pascal single location and 12.500 18 stage pascal single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Special Features:

Black button is marked "20 amp" with silver printing

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0