

View Online at <https://aerobasegroup.com/nsn/5925-01-591-0205>

**Body Style:**

Single pole type

**Overall Length:**

1.379 inches

**Overall Width:**

0.571 inches

**Case Material:**

Plastic

**Mounting Surface To Terminal End Distance:**

1.693 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac single location and 20.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac single location and 250.0 ac single location and 32.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2500.0 ac single location and 2500.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

5.000 at 800 pct pascal single location and 12.500 18 stage pascal single location

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Special Features:**

Black button is marked "20 amp" with silver printing

**Frequency In Hertz:**

60.0 single location

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0