

View Online at <https://aerobasegroup.com/nsn/5925-01-591-4548>

Body Style:

Multipole-multiple actuator type

Bushing Length:

0.130 inches

Body Length:

2.000 inches

Body Width:

1.515 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.558 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.660 inches

End Application:

Misc parts list for lcu 1617

Mounting Surface To Terminal End Distance:

2.032 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded hole

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

80.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Special Features:

Terminals are bus type, 10-32 screws; 50/60 hz; medium delay; black actuator with legend "on-off" in white; ul recognized and csa accepted

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0