

View Online at <https://aerobasegroup.com/nsn/5925-01-591-4564>

**Body Style:**

Multipole-multiple actuator type

**Bushing Length:**

0.130 inches

**Body Length:**

2.000 inches

**Body Width:**

1.515 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.558 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**End Application:**

Misc parts list for lcu 1617

**Mounting Surface To Terminal End Distance:**

2.032 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

4 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

40.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

80.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Special Features:**

Medium delay; black actuator with legend "on-off" in white; terminals are bus type, 10-32 screws; 50/60 hz; ul recognized and csa accepted

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0